
FLOCK

Facestock:

Flock is a highly, dull matte coated paper. Good printing with screen, solvent and water based exo ink systems. Fair letterpress printing with UV ink systems. Not recommended for o-set printing. This facestock can be imprinted.

Basis Weight: 60# per ream +/- 10% (500 sheets 25" x 38")

Caliper: 0.0036 inches +/- 10%

Tensile: MD 32# per inch width CD 17# per inch width

Tear: MD 60 grams per sheet CD 64 grams per sheet

Stiffness: MD 170 mg CD 90 mg

Adhesive:

R5195 is a general-purpose removable adhesive featuring moderate initial tack and minimal adhesion build over time. It offers consistent level of adhesion and long-term removability across a wide variety of substrates.

Type: Emulsion Acrylic

Minimum Application Temperature: +40°F

Service Temperature Range: -65°F to +180°F

Typical Performance Data:

Tested with 60# C1S paper at room temperature on standard lab panels.

Glass:

Loop Tack: 1.0 lbs avg.

Peel Adhesion: 0.9 lbs avg.

Corrugated:

Loop Tack: 0.5 lbs avg.

Peel Adhesion: 0.6 lbs avg.

HDPE:

Loop Tack: 1.0 lbs avg.

Peel Adhesion: 0.75 lbs avg.

Liner:

A bleached super-calendered 40# Kraft stock featuring high internal strength, toughness and tear resistance. Used primarily for roll-to-roll label applications.

Basis Weight: 4.5# per ream +/- 10% (500 sheets 24" x 36")

Caliper: 0.00245 inches +/- 10%

Tensile: MD 41# per inch width CD 17# per inch width

Tear: MD 37 grams CD 45 grams

Total Construction Caliper (Approximate) 0.0069 inches +/- 10%

Shelf Life:

Unless specified otherwise in this document, one year when stored at 70°F at 50% RH

Statement of Practical Use:

As with all pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the specific application.

Ordering Information:

GJ1132 250 - Flocked paper with record folder - 250 per box

GJ1132 500 - Flocked paper with record folder - 500 per box

