



# SHEETING SPECIFICATION

## G-FLEXX FR-7

### MATERIAL SPECIFICATION

<b>DESCRIPTION:</b>	Polyethylene sheeting – reinforced, and flame retardant.
<b>SCRIM:</b>	12 strands per inch in warp direction, HDPE natural yarn. 12 strands per inch in weft or fill direction.
<b>COATING:</b>	Low density polyethylene (LDPE), fire retardant (FR) each side.
<b>TOTAL THICKNESS:</b>	12 mils ± ¼ mil (ASTM D-2103).
<b>WEIGHT:</b>	7 ounces per square yard (ASTM D-1910).
<b>TENSIL STRENGTH:</b>	143.6 lbs warp, 135.7 lbs weft or fill (ASTM D-1683 GRAB).
<b>TEAR STRENGTH:</b>	65 lbs warp, 55 lbs weft or fill (ASTM 2261-71 Tongue Tear)
<b>BURSTING STRENGTH:</b>	265 P.S.I. (ASTM D-3786)
<b>COLOR:</b>	Yellow, Green, White or Natural
<b>FLAME RETARDANT:</b>	NFPA 701 Large Scale

#### ORDERING INFORMATION:

<u>PART#</u>	<u>DESCRIPTION</u>
GA1037	72” x 100 yards, G-Flexx FR-7 polyethylene reinforced sheeting

Specify color: Yellow, Green, White or Natural

