



Sheeting Material Specification

Product:	Sheeting Vinyl 10 oz
Film:	PVC
Reinforcement:	500D x 500D Polyester, 9x9
Standard Embossing:	Matte
Weight:	10.5 oz/sq.
Thickness:	yd. 11 mil
Standard Widths:	54", 61", 72"
Standard Colors:	Green, Yellow, White, custom colors available
Tear Resistance:	Warp: 25# / Fill: 25# (ASTM D-751 Tongue Method)
Adhesion:	22 #/2" (ASTM D-751)
Flame Resistance:	FAR25.853 App.F, Part I (a) (1) (ii)
Tear Resistance:	After-flame under 5 seconds, char length under 7 inches (FED STD 191A TM 5903)
Anti-Mildew:	Yes

***Test results and technical data are typical results, and not minimum standards. The above statements are of opinions that we believe to be accurate and reliable; results are accurate to the best of our knowledge at the time of writing. G/O makes no guarantee of results and assumes no obligation or liability whatsoever in connection with this information. Material is built to meet listed specifications in laboratory settings, and reflects results in industry-accepted lab test environments. Field conditions may vary from test environment. Product should be tested for specific usage by customer. Any person using the above product should first satisfy himself that this product is suitable for his use and meets all required health and safety requirements.

