



Nuclear Grade Duct

CONSTRUCTION

Overall Grade/Function: Premium Nuclear

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	45 lbs/in width	78.8 N/10 mm
Adhesion to Stainless Steel	60 oz/in width	6.57 N/10 mm
Thickness	13 mils	0.33 mm
Elongation	14%	14%
Service Temperature Range	50 F to 200 F	10 C to 93 C

COLOR(S):

Red (RED)

White (WHI)

Yellow (YEL)

Width	Part Number
2"	GZ2239
4"	GZ2240
6"	GZ2241

TYPICAL APPLICATIONS

- For a more robust variety of purposes in the construction, operation and maintenance of nuclear power facilities
- Can also be used for holding to stainless steel pipes, color-coding and sealing endcaps on stainless steel pipes

PRODUCT FEATURES

- Meets ASME NQA-1 guidelines
- Excellent holding power
- Conformable
- High tack

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

