



7500

Glow in the Dark Gaffers

TECHNICAL DATA

TYPICAL APPLICATIONS

- >Gaffer's Tape
- >Safety Marking
- >Various Arts and Entertainment uses

ADVANTAGES AND BENEFITS

- >Glow in the dark - Multiple uses and applications
- >Cloth substrates - hand tearable in both directions
- >High adhesion and tack - strong holding power to many surfaces
- >Clean removal - no adhesive residue
- >Extended glow duration - ideal for safety markings of windowless areas
- >Hand tearable - easy to use

CONSTRUCTION

Overall Grade/Function: Specialty Gaffer's Grade
 Backing: Acrylic coated cloth
 Adhesive: Synthetic Rubber

COLOR(S)

 Glow Green (GLG)

STANDARD WIDTH (S)

24mm 48mm

STANDARD LENGTH (S)

10 yd

Contact your NADCO® sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	48lbs/in width	84.1 N/10mm
Adhesion to Stainless Steel	80 oz/in width	8.76 N/10 mm
Thickness	12.5 mils	0.29 mm
Application Temperature	45 F to 200 F	7 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or NADCO®. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

Conforms to ASTM-D 5486M, Type IV, Class I Specifications - replaced PPP-T-60E, Type IV, Class I (Canceled 1995); A-A-1586A; Conforms to ASTM-D4236.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surface to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

