

DESCRIPTION:

Flexible, polymeric wrap vinyl with repositionable acrylic adhesive back with slidable, lay-flag liner. Opaque surface is printed with UV compound inks. Can be applied by wet or dry application method on the adhesive side. The repositionable adhesive back allows for removability* is ideal for various, finished wall surfaces for decal applications. Use for indoors, and limited 2 years outdoors.

PRODUCT DATA	VALUE	UNIT
<i>Film</i>		
Substrate thickness	3.0	mil
Film weight	105	gsm
Tensile strength	MD > 3500 / CD >3000	lbs/in
Elongation	MD >200 / CD > 200	%
Dimensional stability	MD > .040 mm / CD < .30 mm	FTM 14
<i>Adhesive</i>		
Type	Solvent	
Thickness	1.0 – 1.2	mil
Liner weight	104	lbs/gsm
Liner thickness	8.0	mil
Liner type	white craft	
<i>Adhesion test / Peel strength:</i>		
Stainless Steel -		
15-min dwell time	1.3 / 5.7	lb/in / N/25 mm
24-hr dwell time	2.6 / 11	lb/in / N/25 mm
OEM Painted -		
15-min dwell time	1.1 / 4.4	lb/in / N/25 mm
24-hr dwell time	2.2 / 9.6	lb/in / N/25 mm
<i>Performance Guidelines</i>		
Application temperature	> 40	deg. F
Service Temperature Range	-40 to 200	deg. F
Shelf life	2	years
Storage temperature/Relative humidity	70/50	deg. F/%
Removability (for clean removability*)	2	year

*May require heat. Up to 15% adhesive transfer may occur in certain situations.

PERFORMANCE AND SUITABILITY

Testing can be conducted on the specific materials to accelerate the effects of extended exposure to varied conditions for optical appearance and general properties.

Products can be tested on-site, and at contract testing centers. The descriptive information and performance data provided shall be used as a guide. Furnishing such information is to assist in determining the suitability of the material for the purpose for which it is purchased.

Rev 2025

*G/O Corporation is a distributor for Accuform NMC.

